



## SYSTEM 4500

### TILT-TURN, FIXED – BLAST RESISTANT

The System 4500 tilt-turn and fixed window designs offer builders and architects a very unique product for large openings in both residential and commercial markets. This versatile design is three in one: an inward opening casement in the turn position, a secure top venting hopper in the tilt position and a tightly-sealed picture window when closed. When subjected to 4 and 6 psi blast loading in an Architectural Testing Inc. Security Fenestration Certificate Program, all REHAU System 4500 samples received “No Damage” or “No Hazard” ratings.

**1 Multiple locking points and dual weather seals**

Provide a high level of air and water tightness

**2 Large chambers**

Accommodate reinforcements required in heavy commercial applications for large openings

**3 Accessory groove**

Accepts a variety of accessories such as brickmolds, extension jambs as well as for profiles to couple window elements

**4 Overall 1 in. IG (blast resistant configuration)**

Increases energy efficiency and acoustical properties

**5 3 1/4 in. (82.5 mm) frame depth**

Allows for easy replacement installation

#### Performance Summary

ASTM + GSA: Blast Performance Condition 1 and 2

NAFS-08 CW-100

U-factor down to 0.28-0.32

Up to STC 38

#### GSA/ISC Performance Conditions for Window System Response

Performance	Protection	Hazard Level	Description of Window Glazing Response
1	Safe	None	Glazing does not break. No visible damage to glazing or frame.
2	Very High	None	Glazing cracks but is retained by the frame. Dusting or very small fragments near sill or on floor acceptable.
3a	High	Very Low	Glazing cracks. Fragments enter space and land on floor no further than 3.3 ft from the window.
3b	High	Low	Glazing cracks. Fragments enter space and land on floor no further than 10 ft from the window.
4	Medium	Medium	Glazing cracks. Fragments enter space and land on floor and impact a vertical witness panel at a distance of no more than 10 ft from the window at a height no greater than 2 ft above the floor.
5	Low	High	Glazing cracks and window fails catastrophically. Fragments enter space impacting a vertical witness panel at a distance of no more than 10 ft from the window at a height greater than 2 ft above the floor.

For updates to this publication, visit [na.rehau.com/resourcecenter](http://na.rehau.com/resourcecenter)

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

© 2011 REHAU Printed USA